

- All meta multidirectionnal auto-vibration/shock mounts.
- Exceptional reliability and long life.
- High damping
- No ageing.
- Corrosions resistant.
- Unequalled temperature range : -180°C +300°C.
- Great adaptability/versatility.

Specials on request (material size and number of loops, etc.).

Dimensions are in millimeters. For reference only

SERIES
Materials and finishes (meets RoHS requirements)
<b>AX5</b>
<b>Cable:</b> stainless steel
<b>Interfaces:</b> stainless steel


MODEL			
	height H (mm)	width W (mm)	length L (mm)
-20	15	18	33
-25	18	23	36
-30	21	27	39
-35	23	32	41

STIFFNESS	
Type	
Soft	S
Medium	M
Stiff	R

**A X 5 1 5 S**

SERIE: AX5      MODEL: 15      SUFFIX: S  
 'Axyca' mount from height: Soft type  
 the AX5 series      15mm  
                                  width: 18mm  
                                  length:  
                                  33mm





1. Max static load (F) with corresponding deflection (d)  
2. Max shock load (F) with corresponding deflection (d)  
3. Uncoupled resonant frequency (f) under max static loading 1. and max peak to peak sinusoidal vibration input (2a)

*\*IMPORTANT: Performance characteristics are given here for reference only. They can be increased under specific conditions. Contact us*

COMPRESSION AND SHEAR/ROLL					
AX5 Series soft	Model	-20S	-25S	-30S	-35S
1. Max Static	F daN	1,9	1,5	1,2	1,0
	d mm	1,6	2,0	2,5	3,0
2. Max Shock	F daN	5,7	4,4	3,5	2,9
	d mm	8	11	13	16
3. Max Vibration	2a mm	0,9	1,2	1,5	1,8
	f Hz	13,8	12,0	10,7	9,7
1. Max Static	F daN	1,0	0,7	0,6	0,5
	d mm	2,9	3,9	4,8	5,7
2. Max Shock	F daN	6,2	4,2	3,1	2,4
	d mm	10	13	15	18
3. Max Vibration	2a mm	1,1	1,4	1,7	2,0
	f Hz	12,7	11,2	10,0	9,3

COMPRESSION AND SHEAR/ROLL					
AX5 Series Med	Model	-20M	-25M	-30M	-35M
1. Max Static	F daN	2,3	1,8	1,4	1,2
	d mm	1,6	2,0	2,5	3,0
2. Max Shock	F daN	6,9	5,4	4,3	3,6
	d mm	8	11	13	16
3. Max Vibration	2a mm	0,9	1,2	1,5	1,8
	f Hz	13,6	11,7	10,5	9,5
1. Max Static	F daN	1,2	0,9	0,7	0,6
	d mm	2,9	3,9	4,8	5,7
2. Max Shock	F daN	7,4	5,0	3,7	2,9
	d mm	9	12	14	16
3. Max Vibration	2a mm	1,1	1,3	1,6	1,9
	f Hz	13,0	11,5	10,4	9,5

COMPRESSION AND SHEAR/ROLL					
AX5 Series Stiff	Model	-20R	-25R	-30R	-35R
1. Max Static	F daN	2,8	2,2	1,8	1,5
	d mm	1,6	2,0	2,5	3,0
2. Max Shock	F daN	8,5	6,6	5,3	4,4
	d mm	8	11	13	16
3. Max Vibration	2a mm	0,9	1,2	1,5	1,8
	f Hz	13,3	11,5	10,2	9,2
1. Max Static	F daN	1,4	1,1	0,9	0,7
	d mm	2,9	3,9	4,8	5,7
2. Max Shock	F daN	8,8	6,0	4,4	3,4
	d mm	8	11	13	15
3. Max Vibration	2a mm	1,0	1,2	1,5	1,7
	f Hz	13,5	11,8	10,7	9,8

## TYPICAL SHOCK/VIBRATION SPECIFICATIONS:

Air	AIR 7306, MIL-E-5400, MIL-C-172, MIL-STD-810
Ground Forces	GAM EG13A, SEFT 001, MIL-STD-810, VG 9533
Marine	GAM EG13C, IT25-21/96-31/15-86, MIL-S-167, MIL-S-901, STANAG 042, BV 043.73, BV 044
Others	GAM EMB1, GAM EMBT4, DEF STAN 07-55, IEC 571, FINABEL 2C